



表34 : LFDK-OH , MLFDK-OHシリーズ寸法表

標準型 両シール付	防錆型 両シール付	主 要 寸 法 (mm)															玉 列 数	質 量 (kg)	基本定格荷重	
		d	D	D ₂ h ₁₀	L	ℓ ₁	ℓ ₂	D _f	K	D _p	t	D ₁	T	M	n × S	C (N)			Co (N)	
LFDK6-OH	MLFDK6-OH	6	12	12	35	12.5	5	28	22	20	5	11.4	2	M3	4 × 1.0	4	0.022	354	310	
LFDK8-OH	MLFDK8-OH	8	15	15	45	17.5	5	32	25	24	5	14.4	2	M3	4 × 1.2	4	0.04	419	450	
LFDK10-OH	MLFDK10-OH	10	19	19	55	21.5	6	39	30	29	6	18.4	2	M4	4 × 1.5	4	0.07	865	850	
LFDK12-OH	MLFDK12-OH	12	21	21	57	21.5	7	42	32	32	6	20.4	2	M4	4 × 1.5	4	0.10	892	860	
LFDK13-OH	MLFDK13-OH	13	23	23	60	23	7	43	34	33	6	22.4	2	M4	4 × 1.5	4	0.11	902	870	
LFDK16-OH	MLFDK16-OH	16	28	28	68	26	8	48	37	38	6	27	3	M4	5 × 1.5	5	0.17	1248	1300	
LFDK20-OH	MLFDK20-OH	20	32	32	80	30	10	54	42	43	8	31	3	M5	5 × 2	5	0.23	2083	2020	
LFDK25-OH	MLFDK25-OH	25	40	40	112	42	14	62	50	51	8	39	3	M5	6 × 2	6	0.46	3517	3570	
LFDK30-OH	MLFDK30-OH	30	45	45	122	46	15	74	58	60	10	44	3	M6	6 × 2	6	0.61	5273	5010	
LFDK35-OH	MLFDK35-OH	35	52	52	134	50	17	82	64	67	10	50.5	4	M6	6 × 2	6	0.86	5722	6180	
LFDK40-OH	MLFDK40-OH	40	60	60	153	56.5	20	96	75	78	13	58.5	4	M8	6 × 2.5	6	1.80	7872	8070	