



表15 : LFK-OH , MLFK-OHシリーズ寸法表

標準型 両シール付	防錆型 両シール付	主 要 寸 法 (mm)													玉 列 数	質 量 (kg)	基本定格荷重	
		d	D	L	ℓ	Df	K	Dp	t	D ₁	T	M	n × S	C (N)			Co (N)	
LFK6-OH	MLFK6-OH	6	12	19	5	28	22	20	5	11.4	2	M3	4 × 1.0	4	0.023	218	160	
LFK8-OH	MLFK8-OH	8	15	24	5	32	25	24	5	14.4	2	M3	4 × 1.2	4	0.029	258	220	
LFK10-OH	MLFK10-OH	10	19	29	6	39	30	29	6	18.4	2	M4	4 × 1.5	4	0.061	532	430	
LFK12-OH	MLFK12-OH	12	21	30	7	42	32	32	6	20.4	2	M4	4 × 1.5	4	0.070	549	430	
LFK13-OH	MLFK13-OH	13	23	32	7	43	34	33	6	22.4	2	M4	4 × 1.5	4	0.080	555	440	
LFK16-OH	MLFK16-OH	16	28	37	8	48	37	38	6	27	3	M4	5 × 1.5	5	0.109	768	650	
LFK20-OH	MLFK20-OH	20	32	42	10	54	42	43	8	31	3	M5	5 × 2	5	0.176	1282	1010	
LFK25-OH	MLFK25-OH	25	40	58	14	62	50	51	8	39	3	M5	6 × 2	6	0.30	2164	1790	
LFK30-OH	MLFK30-OH	30	45	64	15	74	58	60	10	44	3	M6	6 × 2	6	0.43	3245	2510	
LFK35-OH	MLFK35-OH	35	52	70	17	82	64	67	10	50.5	4	M6	6 × 2	6	0.59	3521	3090	
LFK40-OH	MLFK40-OH	40	60	80	20	96	75	78	13	58.5	4	M8	6 × 2.5	6	1.21	4844	4040	