



表50 : LH-OH , MLH-OH(グリースニップル付)シリーズ寸法表

標準型 防錆型	主要寸法 (mm)														取付ボルト		玉 列 数	リニアボール ベアリング 番 型	質 量 (kg)	基本定格荷重	
	d	$h^{\pm 0.02}$	W	w	n	$T^{\pm 0.02}$	$t_0$	H	H <sub>1</sub>	H <sub>0</sub>	t	L	ℓ	S <sub>1</sub>	S <sub>2</sub>	C				Co	
LH16-OH MLH16-OH	16	$0$ $-0.009$	19	50	36	7	25	7	37	31.5	12	9	49	34	M5	M4	5	L16-OH ML16-OH	0.20	768	650
LH20-OH MLH20-OH	20	$0$ $-0.010$	21	54	40	7	27	7	41	35	12	11	55	40	M6	M5	5	L20-OH ML20-OH	0.28	1282	1010
LH25-OH MLH25-OH	25		26	76	54	6.5	38	11	51	42.5	18	12	73	50	M8	M6	6	L25-OH ML25-OH	0.65	2164	1790
LH30-OH MLH30-OH	30		30	78	58	6.5	39	10	57	48.5	18	15	80	58	M8	M6	6	L30-OH ML30-OH	0.80	3245	2510
LH35-OH MLH35-OH	35	$0$ $-0.012$	34	92	70	6.5	46	11	65	54	22	20	86	58	M10	M8	6	L35-OH ML35-OH	1.10	3521	3090
LH40-OH MLH40-OH	40		40	102	80	6.5	51	11	75	64	25	22	96	60	M10	M8	6	L40-OH ML40-OH	1.65	4844	4040
LH50-OH MLH50-OH	50		50	130	100	9	65	15	100	85	30	30	124	75	M12	M10	6	L50-OH ML50-OH	3.90	8272	6430
LH60-OH	60	$0$ $-0.015$	55	140	110	9	70	15	110	95	35	35	134	80	M12	M10	6	L60-OH	5.10	9847	7270

