



表52 : LHW-B , MLHW-Bシリーズ寸法表

標準型 防錆型	主要寸法 (mm)													取付ボルト		玉 列 数	リニアボール ベアリング 型 番	質 量 (kg)	基本定格荷重		
	d	$h^{\pm 0.02}$	W	w	n	$T^{\pm 0.02}$	t_0	H	H ₁	H ₀	t	L	ℓ	S ₁	S ₂				C	Co	
LHW10B MLHW10B	10	0 -0.009	13	40	28	7	20	6	26	21.5	10	8	68	46	M5	M4	4	L10-U×2 ML10-U×2	0.18	865	850
LHW12B MLHW12B	12		15	42	30.5	8	21	5.75	29	24	10	8	70	50	M5	M4	4	L12-U×2 ML12-U×2	0.21	892	860
LHW13B MLHW13B	13		15	44	33	7.5	22	5.5	30.5	25	12	9	75	50	M5	M4	4	L13-U×2 ML13-U×2	0.24	902	870
LHW16B MLHW16B	16		19	50	36	7	25	7	37	31.5	12	9	85	60	M5	M4	5	L16-U×2 ML16-U×2	0.40	1248	1300
LHW20B MLHW20B	20	0 -0.010	21	54	40	7	27	7	41	35	12	11	96	70	M6	M5	5	L20-U×2 ML20-U×2	0.57	2083	2020
LHW25B MLHW25B	25		26	76	54	6.5	38	11	51	42.5	18	12	130	100	M8	M6	6	L25B-U×2 ML25-U×2	1.20	3517	3570
LHW30B MLHW30B	30		30	78	58	6.5	39	10	57	48.5	18	15	140	110	M8	M6	6	L30-U×2 ML30-U×2	1.48	5273	5010
LHW35B MLHW35B	35	0 -0.012	34	90	70	6.5	45	10	65	54	22	20	155	120	M8	M6	6	L35-U×2 ML35-U×2	2.20	5722	6180
LHW40B MLHW40B	40		40	102	80	6.5	51	11	75	64	25	22	175	140	M10	M8	6	L40-U×2 ML40-U×2	3.20	7872	8070
LHW50B MLHW50B	50		52	122	100	5	61	11	101	80	25	25	215	160	M10	M8	6	L50-U×2 ML50-U×2	6.70	13442	12860
LHW60B	60	0 -0.015	58	132	108	5	66	12	114	94	25	30	240	180	M12	M10	6	L60-U×2	8.56	16000	14540