

表：LFK, MLFK, ULFK, UMLFKシリーズ寸法表

スタンダード		ウルトラシリーズ		主要寸法 (mm)										玉列数	質量 (kg)	基本定格荷重 C (N)	基本定格荷重 Co (N)
標準型 シールなし 両シール付	防錆型 シールなし 両シール付	標準型 両シール付	防錆型 両シール付	d	D	L	フランジ				S						
							Df	K	t	Dp							
LFK6	MLFK6	ULFK6-UU	UMLFK6-UU	6	12		19	28	22	5	20	M3	4	0.023	218	160	
LFK6-UU	MLFK6-UU																
LFK8	MLFK8	ULFK8-UU	UMLFK8-UU	8	16		25	32	25	5	24	M3	4	0.039	258	220	
LFK8-UU	MLFK8-UU																
LFK8B	MLFK8B	ULFK8B-UU	UMLFK8B-UU	8	15		24	32	25	5	24	M3	4	0.029	258	220	
LFK8B-UU	MLFK8B-UU																
LFK10	MLFK10	ULFK10-UU	UMLFK10-UU	10	19		29	39	30	6	29	M4	4	0.061	532	430	
LFK10-UU	MLFK10-UU																
LFK12	MLFK12	ULFK12-UU	UMLFK12-UU	12	22	0	32	42	32	6	32	M4	4	0.081	549	430	
LFK12-UU	MLFK12-UU			-0.009	-0.021												
LFK12B	MLFK12B	ULFK12B-UU	UMLFK12B-UU	12	21		30	42	32	6	32	M4	4	0.070	549	430	
LFK12B-UU	MLFK12B-UU																
LFK13	MLFK13	ULFK13-UU	UMLFK13-UU	13	23		32	43	34	6	33	M4	4	0.080	555	440	
LFK13-UU	MLFK13-UU																
LFK16	MLFK16	ULFK16-UU	UMLFK16-UU	16	26		36	46	35	6	36	M4	5	0.100	768	650	
LFK16-UU	MLFK16-UU																
LFK16B	MLFK16B	ULFK16B-UU	UMLFK16B-UU	16	28		37	48	37	6	38	M4	5	0.109	768	650	
LFK16B-UU	MLFK16B-UU																
LFK20	MLFK20	ULFK20-UU	UMLFK20-UU	20	32		42	54	42	8	43	M5	5	0.176	1282	1010	
LFK20-UU	MLFK20-UU																
LFK25	MLFK25	ULFK25-UU	UMLFK25-UU	25	40	0	58	62	50	8	51	M5	6	0.300	2164	1790	
LFK25-UU	MLFK25-UU			-0.010	-0.025												
LFK30	MLFK30	ULFK30-UU	UMLFK30-UU	30	47		64	76	60	10	62	M6	6	0.55	3245	2510	
LFK30-UU	MLFK30-UU																
LFK30B	MLFK30B	ULFK30B-UU	UMLFK30B-UU	30	45		64	74	58	10	60	M6	6	0.43	3245	2510	
LFK30B-UU	MLFK30B-UU																
LFK35	MLFK35	ULFK35-UU	UMLFK35-UU	35	52		70	82	64	10	67	M6	6	0.59	3521	3090	
LFK35-UU	MLFK35-UU																
LFK40	MLFK40	ULFK40-UU	UMLFK40-UU	40	60	0	80	96	75	13	78	M8	6	1.21	4844	4040	
LFK40-UU	MLFK40-UU			-0.012	-0.030												
LFK50	MLFK50	ULFK50-UU	UMLFK50-UU	50	80		100	116	92	13	98	M8	6	1.99	8272	6430	
LFK50-UU	MLFK50-UU																
LFK60	MLFK60	ULFK60-UU	UMLFK60-UU	60	90	0	110	134	106	18	112	M10	6	3.20	9847	7270	
LFK60-UU	MLFK60-UU			-0.015	-0.035												

呼び番号 U LFK20 -UU -G -4-M5×20

ウルトラ


標準型	
M-防錆型	
シール	
無記号	シールなし
UU	両シール付

グリース

無記号	グリースなし
G	標準グリース
CG	クリーングリース
VG	真空グリース
HG	高温グリース
FG	食品グリース

※グリースの性状P44参照

ボルト本数-ボルトサイズ



推奨六角穴付ボルト

軸径 (d)	六角穴付ボルト	
	呼び径	長さ
6, 8	M3	10, 12, 16
10~16	M4	12, 16, 20
20, 25	M5	16, 20, 25
30, 35	M6	20, 25, 30
40, 50	M8	25, 30, 35
60	M10	35, 40, 45

※上記以外の長さをご希望の場合は、別途お問い合わせ下さい。