



表：MSKシリーズ寸法表

ナット型番	リード	主 要 寸 法					
		D	Df	PCD	K	L	T
MSK 0401	1	10	23	15	15	11.5	3.5
MSK 0402	2						
MSK 0601	1	12	26	18	17	14.5	3.5
MSK 0602	2						
MSK 0609	9						
MSK 0618	18						
MSK 0801	1	14	29	21	18	18	4
MSK 0802	2						
MSK 0812	12						
MSK 0824	24						
MSK 1002	2	16	33	24	21	22	5
MSK 1006	6						
MSK 1010	10						
MSK 1015	15						
MSK 1030	30	18	35	26	22	25	5
MSK 1202	2						
MSK 1204	4						
MSK 1208	8						
MSK 1212	12						
MSK 1218	18						
MSK 1236	36						
MSK 1505	5						
MSK 1510	10						
MSK 1520	20						
MSK 2010	10						
MSK 2020	20	30	50	40	32	36	7

単位：mm

寸 法	S	許容スラスト荷重 Fa (N)	許容回転数 Nc (rpm)	最大締付け トルク (N・mm)	質 量 (g)	ステンレス ネジ軸型番	ネジ軸主要寸法			質 量 (kg/m)
							d	谷径 d ₁	標準軸長 ℓ	
2.9	1	50	2000	180	2.09	MS 0401	4	3.3	200	0.08
	2	60			2.09					MS 0402
3.4	1	120	2000	400	2.89	MS 0601	6	5.3	300	0.19
		60			2.86					MS 0602
	4	90			2.80	MS 0609		0.21		
		70			2.77	MS 0618		0.21		
3.4	1	200	2000	400	4.00	MS 0801	8	7.3	300	0.35
		290			4.08					MS 0802
	4	210			3.97	MS 0812		0.34		
		210			3.94	MS 0824		0.36		
4.5	1	460	1500	500	5.90	MS 1002	10	8.6	300	0.52
		370			5.78					MS 1006
	4	250			5.76	MS 1010		0.54		
		410			5.83	MS 1015		0.52		
	6	410			5.94	MS 1030		0.50		
4.5	1	660	1000	500	7.24	MS 1202	12	10.6	1000	0.77
		620			7.48					MS 1204
	2	820			7.46	MS 1208		0.73		
		470			7.08	MS 1212		0.82		
	6	750			7.17	MS 1218		0.77		
		540			7.10	MS 1236		0.80		
4.5	1	890	800	500	16.39	MS 1505	15	12.2	2000	1.15
	2	1040			15.73					MS 1510
	4	1100			16.44	MS 1520		1.14		
5.5	2	1240	600	600	25.76	MS 2010	20	17.5	2000	2.16
	4	1420			26.35					MS 2020

呼び番号 ナット型番 ネジ軸型番
 MSK 08 02 + MS 0802 - 300
 ネジ軸外径 + MSC0802 - 150
 リード + MSP0802 - 200
 ネジ軸の種類 ネジ軸長さ